

# PRODUCT DATA SHEET



High-performance special adhesive tape for linoleum

# Linomur 45



Does not become brittle, secure and permanent bond

Secure installation of linoleum skirting strips

## Areas of application:

Special acrylate adhesive system for quick and secure installation of linoleum skirting up to 3.2 mm thickness. Linomur allows quick and clean working without solvents. For interior applications.

### ► Suitable for:

- Linoleum skirting strips

### ► Suitable for use on:

- Plaster
- Brickwork
- Metal (untreated)
- Painted surfaces
- Plastics
- Wood
- Concrete
- Ceramics
- Gypsum (primed)
- Wallpaper\*
- Levelling compound (primed)

\* see „Notes for preparation“

Request application consulting for other materials.

Item	Sheet width	Strips
Linomur 45	45 mm	50 mm

Provides the highest possible level of emission safety and contributes towards creating a healthy room climate. Marked with the "Blue Angel" for low-emission floor covering adhesives and other installation materials according to RAL-UZ 113.



[www.bauer-engel.de/uz113](http://www.bauer-engel.de/uz113)

## ÖKOLINE

for linoleum skirting

ON substrates up to 1.5 mm structure height

**Constituents:** Acrylic copolymers, wetting and defoaming agents, laid scrim, paper

## Product benefits / properties:

- Does not become brittle, secure and permanent bond
- Clean & fast
- Solvent-free
- "Blue Angel" as per RAL-UZ 113
- EMICODE EC1 PLUS/very low-emission

## Technical data:

Packaging:	Carton
Width of rolls:	45 mm
Length of rolls:	50 m
Shelf life:	min. 2 years
Colour:	transparent
Substrate temperature:	min. 18 °C
Open time:	none
Working time:	unlimited
Set to traffic:	immediately after bonding
Sealing/jointing seams:	immediately after bonding

UZIN | A brand of Uzin Utz Group

DE | Uzin Utz AG | Dieselstraße 3 | 89079 Ulm | Telefon +49 731 4097-0 | Telefax +49 731 4097-110 | E-Mail [info@uzin.de](mailto:info@uzin.de) | Internet [www.uzin.com](http://www.uzin.com)

GB | Uzin Utz UK Ltd. | Unit 2, Mitchell Court | Central Park, Rugby, CV23 0UY | Tel.: +44 1788 530 080 | Fax: +44 1788 536 508 | E-mail: [uzin.uk@uzin-utz.com](mailto:uzin.uk@uzin-utz.com) | Internet [www.uzin.co.uk](http://www.uzin.co.uk)  
Developed and manufactured | Sifloor AG

## Notes for preparation:

- ▶ The substrate must be permanently dry, hard, load-bearing, flat, free from grease, dust and silicon, in accordance with the respective national standards (EN, DIN, VOB, OE, SIA).
- ▶ Wallpaper must be firmly bonded or cut / removed for the height covered by the skirting.
- ▶ Bind dust with a solvent-free primer (e.g. UZIN PE 260).
- ▶ The floor covering and Linomur must be adequately free from tension before installation and acclimatized to the indoor climate.

## The following is needed:


- ▶ Linomur, pressure roller (rubbing tool), rubbing hammer, carpet knife



## Installing linoleum skirting strips:



- ▶ Cut strips of linoleum skirting to size and attach Linomur on the back of the linoleum in longitudinal direction. Then apply pressure across the back.



- ▶ Pull off the protective paper



- ▶ Install the linoleum ensuring it is free from tension and strain



- ▶ Fully rub over the linoleum while applying pressure
- ▶ The joint between the floor covering and skirting can be sealed immediately with sealing compound or joint mastic

## Important notes:

Store in a dry, cool area and without exposure to direct sunlight.

Skirting strips can only be installed once adequately relieved from tension.

The skirting strips must be cut to size in longitudinal direction.

## Protection of the workplace and the environment:

The product does not require any special labour protection measures. For reasons of working hygiene, we recommend avoiding eating, drinking and smoking during processing of this product. Store out of the reach of children.

For more information refer to [www.uzin.de](http://www.uzin.de) or contact +49 (0)731 4097-0

## Disposal:

Sleeves and carton packaging free from residues can be recycled. Material residues can be disposed of with domestic waste.

## Warranty:

**UZIN grants a 5-year warranty for all properties claimed in the processing instructions.**

- Follow the generally acknowledged rules of the trade and of technology for the installation of floor covering of the respective applicable standards (EN, DIN, VOB, OE, SIA)

Suitable bonding tests must be performed at any rate on site before processing.

The warranty becomes void if:

- the product is exposed to unusual impact especially of chemical or mechanical nature.
- used or processed differently than stated in the installation instructions.
- the floor covering was installed under pulling forces or tension.
- Linomur is exposed to moisture.
- installation was performed below 18°C (on the wall).
- Linomur is used in areas with increased humidity or thermal exposures (e.g. conservatories).