

PRODUCT DATA SHEET



High-performance special adhesive tape for linoleum

Linomur 90



Secure installation of curved linoleum skirting and linoleum skirting strips

Areas of application:

Special acrylate adhesive system for quick and secure installation of curved linoleum skirting and linoleum skirting strips up to 3.2 mm thickness. Linomur allows quick and clean working without solvents. For interior applications.

► Suitable for:

- Linoleum skirting strips
- Prefabricated curved linoleum skirting

► Suitable for use on:

- Plaster
- Brickwork
- Metal (untreated)
- Painted surfaces
- Plastics
- Wood
- Concrete
- Ceramics
- Gypsum (primed)
- Wallpaper*
- Levelling compound (primed)

* see "Notes for preparation"

Request application consulting for other materials.

Item	Sheet width	Position
Linomur 90	90 mm	for wall
Linomur 90	90 mm	for floor

Provides the highest possible level of emission safety and contributes towards creating a healthy room climate. Marked with the "Blue Angel" for low-emission floor covering adhesives and other installation materials according to RAL-UZ 113.



www.bauer-engel.de/uz113

ÖKOLINE

for linoleum skirting and linoleum coving profiles

ON substrates up to 1.5 mm structure

Constituents: Acrylic copolymers, wetting and defoaming agents, laid scrim, paper

Product benefits / properties:

- Does not become brittle, secure and permanent bond
- Clean & fast
- Solvent-free
- "Blue Angel" as per RAL-UZ 113
- EMICODE EC1 PLUS / very low-emission

Technical data:

Packaging:	Carton
Width of rolls:	90 mm
Length of rolls:	50 m
Shelf life:	min. 2 years
Colour:	transparent
Substrate temperature:	min. 18 °C
Open time:	none
Working time:	unlimited
Set to traffic:	immediately after bonding
Sealing / jointing seams:	immediately after bonding

UZIN | A brand of Uzin Utz Group

DE | Uzin Utz AG | Dieselstraße 3 | 89079 Ulm | Telefon +49 731 4097-0 | Telefax +49 731 4097-110 | E-Mail info@uzin.de | Internet www.uzin.com

GB | Uzin Utz UK Ltd. | Unit 2, Mitchell Court | Central Park, Rugby, CV23 0UY | Tel.: +44 1788 530 080 | Fax: +44 1788 536 508 | E-mail: uzin.uk@uzin-utz.com | Internet www.uzin.co.uk
Developed and manufactured | Sifloor AG

Notes for preparation:

- ▶ The substrate must be permanently dry, hard, load-bearing, plane, free from grease, dust and silicon, in accordance with the respective national standards (EN, DIN, VOB, OE, SIA).
- ▶ Wallpaper must be firmly bonded or cut / removed for the height covered by the skirting.
- ▶ Bind dust with a solvent-free primer (e.g. UZIN PE 260).
- ▶ The floor covering and Linomur must be adequately free from tension before installation and acclimatized to the indoor climate.

The following is needed:

- ▶ Linomur, pressure roller (rubbing tool), rubbing hammer, carpet knife



Installing curved linoleum skirting:



- 1 ▶ Mark skirting height (10 cm) on the wall
- ▶ Affix Linomur flush to the marking on the wall




- 2 ▶ In addition, apply a strip of Linomur at a distance of approx. 2 cm from the wall on the floor



- 3 ▶ Loosely put down the curved skirting and cut the protective paper along the edge



- 4 ▶ Remove the protective paper from the floor section
- ▶ Place curved element against the wall and put down on the floor with exact fit




- 5 ▶ Thoroughly roll / rub over the floor section
- ▶ Fold the loose wall section forward
- ▶ Remove the protective paper from the wall section



- 6 ▶ Fold up the wall section and thoroughly roll / rub over
- ▶ Roll out the sheets and fold back half way



- 7 ▶ Spread the adhesive both on the substrate and (partially) on the protective paper with a notched trowel
- ▶ Remove the protective paper immediately



- 8 ▶ Slide the floor covering in place and rub / roll over

Important notes:

Store in a dry, cool area and without exposure to direct sunlight. Skirting strips can only be installed once adequately relieved from tension (only as an upstanding).

Skirting strips must be cut to size in longitudinal direction.

Installation instructions for linoleum skirting strips is described in the Linomur® 45 data sheet.

Protection of the workplace and the environment:

The product does not require any special labour protection measures. For reasons of working hygiene, we recommend avoiding eating, drinking and smoking during processing of this product. Store out of the reach of children.

For more information refer to www.uzin.de or contact +49 (0)731 4097-0

Disposal:

Sleeves and carton packaging free from residues can be recycled. Material residues can be disposed of with domestic waste.

Warranty:

UZIN grants a 5-year warranty for all properties claimed in the processing instructions.

- Follow the generally acknowledged rules of the trade and of technology for the installation of floor covering of the respective applicable standards (EN, DIN, VOB, OE, SIA)

Suitable bonding tests must be performed at any rate on site before processing.

The warranty becomes void if:

- the product is exposed to unusual impact especially of chemical or mechanical nature
- used or processed differently than stated in the installation instructions.
- the floor covering was installed under pulling forces or tension.
- Linomur is exposed to moisture.
- installation was performed below 18 °C (on the wall).
- Linomur is used in areas with increased humidity or thermal exposures (e.g. conservatories).