

# PRODUCT DATA SHEET



Premium 2-Component Scratch Concealer

# UZIN Refresher

2-component spot scratch concealer for resilient floorings with a polyurethane wear layer

## Description:

UZIN Refresher is a premium 2-component product ideal for concealing scratches and white marks on most resilient floor coverings manufactured with a polyurethane wear layer. For interior use only.

## Suitable for:

- ▶ Resilient flooring with a polyurethane wear layer
- ▶ LVT (Luxury Vinyl Tile)
- ▶ LVP (Luxury Vinyl Plank)
- ▶ Linoleum (with polyurethane wear layer)
- ▶ Any floor coated with UZIN Turbo Protect Plus
- ▶ 2-component oiled wooden surfaces
- ▶ Interior residential (apartments, homes)
- ▶ Interior commercial (offices, hospitals, schools, hotels, stores, assisted living, universities)



## Product benefits / properties:

UZIN Refresher is a 2-component scratch concealer that is easy to apply. Exceptional finish on most resilient floors manufactured with a polyurethane wear layer. It is formulated for residential and commercial applications.

- ▶ Extremely durable
- ▶ Excellent coverage
- ▶ Fast drying and curing
- ▶ Scratch concealing
- ▶ Reduces labour costs
- ▶ Immediate problem solver when time constraints are an issue
- ▶ Excellent finish

Before:



After:



## Technical Data:

Packaging:	Comp. A: 80 ml metal can Comp. B: 20 ml plastic bottle
Shelf life:	12 months
Odour:	neutral
Coverage:	approx. 100 m <sup>2</sup>
Working temperature:	min. 15°C at floor level
Mixing ratio:	4:1 (A:B)
Working time:	approx. 4 hours after Comp. B is added*
Set to traffic:	approx. after 3 – 4 hours*
Fully Cured:	approx. after 3 – 4 hours*

\*At 21°C and 65% relative humidity.  
Coverage is approximate and could vary depending on substrate.

UZIN | A brand of Uzin Utz Group

DE | Uzin Utz AG | Dieselstraße 3 | 89079 Ulm | Telefon +49 731 4097-0 | Telefax +49 731 4097-110 | E-Mail info@uzin.de | Internet www.uzin.com

GB | Uzin Utz UK Ltd. | Unit 2, Mitchell Court | Central Park, Rugby, CV23 0UY | Tel.: +44 1788 530 080 | Fax: +44 1788 536 508 | E-mail: uzin.uk@uzin-utz.com | Internet www.uzin.co.uk

FR | Uzin Utz France SAS | 6 avenue du Professeur André Lemierre | 75980 Paris Cedex 20 | Téléphone +33 141632720 | Téléfax +33 141632721 | E-mail uzin.fr@uzin-utz.com | Internet www.uzin.fr

## Substrate preparation:

- ▶ Before using read all instructions and product safety data sheet for both components.
- ▶ The floor must be structurally sound, solid, dry, clean and free of all contaminants such as grease, oil, paint and wax. Use RZ Handpads black or similar pads, and if needed use UZIN Basic Cleaner.

## Application:

- ▶ Before use, allow the contents of the containers to come to room temperature.
- ▶ Shake well. Add Component B to Component A. Use one part Comp. B to 4 parts Comp. A using the supplied plastic spoon as the unit of measure. Mix vigorously with a clean mixing stick for at least 30 seconds.
- ▶ Use a clean mixing stick to drop the concealer directly onto scratched or damaged part of the floor. Start with a small amount of concealer and add more as needed.
- ▶ Use a red hand pad to buff product into all the scratches and white lines. Can also be done with the WOLFF Disc holder for pads or standard 400 mm buffer and red pad.
- ▶ Use a cotton cloth to polish the surface and to remove the concealer from the unscratched parts of the floor. Can also be done with the WOLFF Disc holder for pads or standard 400 mm buffer with the cotton cloth under a red pad.
- ▶ Continue polishing as needed to eliminate any sheen difference between the concealer and floor.
- ▶ Clean tools with water immediately after use.

## Important notes:

- ▶ Shelf life: minimum 12 months when stored in original packaging at 23 °C. Protect from freezing. Tightly re-seal opened packages. After the packages have been opened, the material must be used up within 3 months. Allow product to reach room temperature before use.
- ▶ The curing process takes approximately 3 – 4 hours. Wait until fully cured before using any cleaners or before replacing rugs and mats.
- ▶ Optimum working conditions are 20 – 25 °C room temperature, minimum floor temperature of 16 °C and relative humidity below 65 %. Low temperatures and high humidity delay, while high temperatures and low humidity shorten the working time.
- ▶ Glides/Protectors should be installed and maintained on all moveable chairs, tables, fixtures and other furniture to protect the coatings from unnecessary scratching.
- ▶ For Interior use only.

## Protection of the Workplace and the Environment:

Component A: Non-flammable but risk of spontaneous combustion (see "Important Note"). Component B: Non-flammable. Contains isocyanates. Harmful by inhalation. May cause an allergic skin reaction. Irritating to respiratory system. May cause sensitisation by skin contact. Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water and soap. Wear suitable gloves and eye/face protection. Provide good ventilation. If swallowed, seek medical advice immediately and show this container or label. Observe safety information on product label as well as safety data sheet.

**Important Note:** Abrasive dust of oxygen-drying systems are inflammatory. Fire risk! After conclusion of sanding works the resulted abrasive dust must be damped with water and be disposed into closely locked metal containers! Contact of this product with pads or textile materials leads to the risk of spontaneous combustion! Therefore, soak any contaminated cloths, pads, etc. with water and store or dispose in tightly sealed metal containers.

## Disposal:

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty, drip-free containers are recyclable. Containers with liquid residue, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste.