

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** UZIN RK 37
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU19 Building and construction work
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 For professional use only.
- **Product category** PC1 Adhesives, sealants
- **Application of the substance / the mixture** 1-Component PU Spot-Fix Adhesive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Uzin Utz UK Ltd.
 Unit 2, Mitchell Court
 Central Park, Rugby
 Warwickshire, CV23 0UY,
 Telephone +44 (0) 1788 530 080
 Fax +44 (0) 1788 536508
 Email info@uk.uzin-utz.com
- **Further information obtainable from:**
 Product safety department
 email: msds.info@uzin-utz.com
- **1.4 Emergency telephone number:**
 Medical emergencies (GIZ-Nord Poisons Center): +49 551 19240
 Transportation emergencies: +49 621 60 43 333

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

- Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 Carc. 2 H351 Suspected of causing cancer.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

- Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS07, GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**
 Diphenylmethanediisocyanate, isomeres and homologues

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

Trade name: UZIN RK 37

(Contd. of page 1)

Hazard statements

- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- P201 Obtain special instructions before use.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· **Description:** 1-component PU-Adhesive

Dangerous components:

CAS: 9016-87-9	Diphenylmethanediisocyanate, isomeres and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	75-100%
----------------	---	---------

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Asthma attacks

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

Trade name: UZIN RK 37

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Wear suitable protective clothing, gloves and eye/face protection.
Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Keep away from foodstuffs, beverages and feed.
Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.
Wash hands before breaks and at the end of work.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from humidity and water.
Once opened unfinished quantities must be stored in airtight packaging conditions.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

Trade name: UZIN RK 37

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 9016-87-9 Diphenylmethanediisocyanate, isomeres and homologues

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Wear suitable protective clothing, gloves and eye/face protection.

Keep away from foodstuffs, beverages and feed.

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary. Ensure that room is well-ventilated during processing.

Respiratory protection required in insufficiently ventilated working areas. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter is recommended (A2-P2).

· Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability (EN 374)

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles (EN 166)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Brown
Odour:	Light

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

· **Flash point:** > 200 °C

· **Ignition temperature:** > 400 °C

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

Trade name: UZIN RK 37

(Contd. of page 4)

· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Vapour pressure at 20 °C:	< 0.0001 hPa
· Density at 20 °C:	1.1 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity:	
Dynamic at 20 °C:	7000 mPas
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
From approx. 260°C, polymerization and separation of CO₂
- **10.3 Possibility of hazardous reactions**
May produce violent reactions with bases and numerous organic substances including alcohols and amines.
The product reacts slowly with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.
- **10.4 Conditions to avoid** Avoid heating to above 40°C and cooling to below 10°C.
- **10.5 Incompatible materials:**
Uncontrolled exothermic reactions occur with amines and alcohols.
During storage, avoid moisture contamination.
- **10.6 Hazardous decomposition products:**
In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomer isocyanates, amines and alcohols may be produced.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **Additional toxicological information:**
Based on the properties of the isocyanate components and considering toxicological data on similar preparations, this preparation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Diphenylmethane-diisocyanate, isomers and homologues
Carcinogenicity: May cause cancer by inhalation. On the basis of these data classification as carcinogenic is therefore required (H351).
Mutagenicity: In vitro and in vivo tests did not show mutagenic effects.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

Trade name: UZIN RK 37

(Contd. of page 5)

- *Teratogenicity: Did not show teratogenic effects in animal experiments.*
- *Reproductive toxicity/Fertility: Based on available data, the classification criteria are not met.*
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
*Do not allow product to reach sewage system.
Let product residues harden in open container, then dispose of as construction waste.
Disposal should be in accordance with local, state or national legislation.*
- **Uncleaned packaging:**
- **Recommendation:**
*Disposal must be made according to official regulations.
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.*

SECTION 14: Transport information

- | | |
|---|------|
| · 14.1 UN-Number
· ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name
· ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es)
· ADR, ADN, IMDG, IATA
· Class | Void |
| · 14.4 Packing group
· ADR, IMDG, IATA | Void |

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

Trade name: UZIN RK 37

(Contd. of page 6)

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications. Avoid heating to above 40°C and cooling to below 10°C.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3**
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Recommended restriction of use** For professional use only.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Contact:**

Dr. M. Zieger, phone +49 (0)731 4097 207
E-Mail: msds.info@uzin-utz.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.11.2018

Version No. 4

Revision: 27.11.2018

Trade name: UZIN RK 37

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. of page 7)

· * **Data compared to the previous version altered.**

GB